

ENGLISH
FRANÇAIS
ESPAÑOL

NEW • NOUVEAUTÉ
NOVEDAD

REX 4

70-80-90-100-110-120 F/GE/GB/GT



		REX 4-070	REX 4-080	REX 4-090	REX 4-100	REX 4-110	REX 4-120
		F/GE/GB	F/GE/GB/GT	F/GE/GB/GT	F/GE/GB/GT	F/GE/GB/GT	F/GE/GB/GT
ENGINE							
DEUTZ TIER 4 INTERIM		2,9 TCD L4	2,9 TCD L4	2,9 TCD L4	2,9 TCD L4	2,9 TCD L4	2,9 TCD L4
MAX POWER ISO	HP/KW	70/52	76/56	90/66	95/70	102/75	112/82
RATED SPEED	RPM	2200	2200	2200	2200	2200	2200
MAX TORQUE	NM	272	300	378	400	410	420
DISPLACEMENT/N° OF CYLINDERS	CM³	2900/4 TA	2900/4 TA	2900/4 TA	2900/4 TA	2900/4 TA	2900/4 TA
FUEL TANK CAPACITY F,GE,GB / GT	LT	65	65/85	65/85	65/85	65/85	65/85
ENGINE MEMO SWITCH		●	●	●	●	●	●
CLUTCH							
INDEPENDENT DRY DUAL CLUTCH	IN.	11	11	12	12	12	12
MECHANICALLY OPERATED		●	●	●	●	●	●
MULTI-DISC WET CLUTCH		○	○	○	○	○	○
DE-CLUTCH CONTROL: BUTTON-OPERATED CLUTCH		○	○	○	○	○	○
TRANSMISSION							
SPEED FOUR+SYNCHRO SHUTTLE: 12FWD+12REV		●	●	●	●	●	●
SPEED FOUR+CREEPER+SYNCHRO SHUTTLE: 16FWD+16REV		○	○	○	○	○	○
SPEED FIVE + SYNCHRO SHUTTLE: 15FWD+15REV		○	○	○	○	○	○
SPEED FIVE + CREEPER + SYNCHRO SHUTTLE: 20FWD+20REV		○	○	○	○	○	○
SPEED FIVE + REVERSE POWER SHUTTLE: 15FWD+15REV		○	○	○	○	○	○
SPEED FIVE + CREEPER + REVERSE POWER SHUTTLE: 20FWD+20REV		○	○	○	○	○	○
SPEED FIVE + POWERFIVE + REVERSE POWER SHUTTLE: 30FWD+30REV		○	○	○	○	○	○
SPEED FIVE + POWERFIVE+ CREEPER + REVERSE POWER SHUTTLE: 40FWD+40REV		○	○	○	○	○	○
POWER TAKE-OFF							
POWER ASSISTED MECHANICAL ENGAGEMENT		●	●	●	●	●	●
1 SPEEDS 540 RPM		●	●	●	●	●	●
2 SPEEDS 540/750 RPM		○	○	○	○	○	○
2 SPEEDS 540/1000 RPM		○	○	○	○	○	○
1"3/8 (34,9 MM) PTO SHAFT WITH 6 SPLINES		●	●	●	●	●	●
GROUND SPEED PTO		○	○	○	○	○	○
4WD FRONT AXLE							
ELECTROHYDRAULIC 4WD ENGAGEMENT		●	●	●	●	●	●
MAX. STEERING ANGLE 55°		●	●	●	●	●	●
DIFF-LOCKS LIMITED SLIP		●	●	●	●	●	●
100% TWIN-LOCK ELECTROHYDRAULIC DIFF-LOCKS		○	○	○	○	○	○
BRAKES							
WET MULTI-DISK REAR BRAKES		●	●	●	●	●	●
AUTOMATIC 4WD ENGAGEMENT ON BRAKING		●	●	●	●	●	●
WET MULTI-DISK FRONT BRAKES WITH AXLE HYDRALOCK		○	○	○	○	○	○
HYDRAULIC TRAILER BRAKES		○	○	○	○	○	○
HYDRAULIC POWER LIFT							
DRAFT, POSITION, INTERMIX AND FLOATING CONTROL		●	●	●	●	●	●
MECHANICALLY OPERATED		●	●	●	●	●	●
STD LIFTING CAPACITY	KG	2600	2600	2600	2600	2600	2600
ADDITIONAL CAPACITY WITH 1 ASSISTOR RAM (ONLY FOR GT MOD.)	KG	-	3250	3250	3250	3250	3250
TOTAL HYDRAULIC FLOW (POWER LIFT+ STEERING)	LT/MIN	50+28	50+28	50+28	50+28	50+28	50+28
CAT. 2 THREE-POINT LINKAGE		●	●	●	●	●	●
HYDRAULIC ADJUSTMENT OF RIGHT LIFTING ROD		○	○	○	○	○	○
AUXILIARY VALVES STD		1	1	1	1	1	1
DRIVING SEAT							
SUSPENDED PLATFORM		●	●	●	●	●	●
TELESCOPIC ADJUSTABLE STEERING COLUMN		○	○	○	○	○	○
DIMENSIONS AND WEIGHTS WITH TYRES							
FRONT TYRES 4WD		280/70R16 / 260/70R16	280/70R16 / 260/70R16 / 7.50-18	280/70R16 / 260/70R16 / 7.50-18	280/70R16 / 260/70R16 / 7.50-18	280/70R16 / 260/70R16 / 7.50-18	280/70R16 / 260/70R16 / 7.50-18
REAR TYRES		14.9R24 / 14.9LR20	14.9R24 / 14.9LR20 / 14.9R24	14.9R24 / 14.9LR20 / 14.9R24	14.9R24 / 14.9LR20 / 14.9R24	14.9R24 / 14.9LR20 / 14.9R24	14.9R24 / 14.9LR20 / 14.9R24
LENGTH 4WD	MM	4009 / 4009	4009 / 4009 / 4009	4009 / 4009 / 4009	4009 / 4009 / 4009	4009 / 4009 / 4009	4009 / 4009 / 4009
MIN. WIDTH 4WD F / GE,GB / GT	MM	1437 / 1413	1437 / 1413 / 1554	1437 / 1413 / 1554	1437 / 1413 / 1554	1437 / 1413 / 1554	1437 / 1413 / 1554
WHEELBASE 4WD	MM	2134	2134	2134	2134	2134	2134
HEIGHT TO ROPS	MM	2315 / 2150	2315 / 2150 / 2315	2315 / 2150 / 2315	2315 / 2150 / 2315	2315 / 2150 / 2315	2315 / 2150 / 2315
GROUND CLEARANCE 4WD	MM	220 / 190	220 / 190 / 240	220 / 190 / 240	220 / 190 / 240	220 / 190 / 240	220 / 190 / 240
WEIGHT 4WD (WITHOUT BALLAST) F / GE,GB / GT	KG	2845 / 2540	2845 / 2540 / 2865	2845 / 2540 / 2865	2845 / 2540 / 2865	2845 / 2540 / 2865	2845 / 2540 / 2865
OPTIONAL EQUIPMENT							
6 FRONT WEIGHTS 36 KG EACH		○	○	○	○	○	○
4 FRONT WEIGHTS 42 KG EACH		○	○	○	○	○	○

Key: ● standard ○ option – not available

All data and illustrations provided in this brochure are for information purposes only and can be changed without notice.