





Electric three-wheel counterbalanced forklift truck


EFG 110-115

Lift height: 2.300-6500 mm / Capacity: 1.000-1500 kg

EFG 110-115



EFG 110-115



EFG 110-115

EFG 110 soloPILOT, EFG 110 multiPILOT, EFG 113 soloPILOT, EFG 113 multiPILOT, EFG 115 soloPILOT, EFG 115 multiPILOT	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Tilt of mast forwards/backwards
Triplex mast DZ	6000 mm	2555 mm	2005 mm	6550 mm	5 / 4 °
EFG 110k soloPILOT, EFG 110k multiPILOT, EFG 110 soloPILOT, EFG 110 multiPILOT, EFG 113 soloPILOT, EFG 113 multiPILOT, EFG 115 soloPILOT, EFG 115 multiPILOT	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Tilt of mast forwards/backwards
Duplex mast ZT	2300 mm	1650 mm	150 mm	2850 mm	5 / 4 °
	3000 mm	2000 mm	150 mm	3550 mm	5 / 6 °
	3100 mm	2050 mm	150 mm	3650 mm	5 / 6 °
	3300 mm	2150 mm	150 mm	3850 mm	5 / 6 °
	3600 mm	2300 mm	150 mm	4150 mm	5 / 6 °
	4000 mm	2500 mm	150 mm	4550 mm	5 / 6 °
	4500 mm	2800 mm	150 mm	5050 mm	5 / 6 °
	5000 mm	3050 mm	150 mm	5550 mm	5 / 5 °
Duplex mast ZZ	2300 mm	1605 mm	1055 mm	2850 mm	5 / 4 °
	3000 mm	1955 mm	1405 mm	3550 mm	5 / 6 °
	3100 mm	2005 mm	1455 mm	3650 mm	5 / 6 °
	3300 mm	2105 mm	1555 mm	3850 mm	5 / 6 °
	3600 mm	2255 mm	1705 mm	4150 mm	5 / 6 °
	4000 mm	2455 mm	1905 mm	4550 mm	5 / 6 °
Triplex mast DZ	4350 mm	1955 mm	1405 mm	4900 mm	5 / 6 °
	4500 mm	2005 mm	1455 mm	5050 mm	5 / 6 °
	4800 mm	2105 mm	1555 mm	5350 mm	5 / 6 °
	5000 mm	2180 mm	1630 mm	5550 mm	5 / 5 °
	5250 mm	2255 mm	1705 mm	5800 mm	5 / 5 °
	5500 mm	2355 mm	1805 mm	6050 mm	5 / 5 °
EFG 113 soloPILOT, EFG 113 multiPILOT, EFG 115 soloPILOT, EFG 115 multiPILOT	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Tilt of mast forwards/backwards
Triplex mast DZ	6500 mm	2805 mm	2255 mm	7050 mm	5 / 4 °

VDI table

Stand-on: 06/2020

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich			
	1.2	Manufacturer's type designation		EFG 110k	EFG 110	EFG 113	EFG 115
	1.3	Drive		Electric			
	1.4	Operation		Seat			
	1.5	Capacity/load	Q kg	1.000		1.250	1.500
	1.6	Load centre distance	c mm	500			
	1.8	Load distance, centre of drive axle to fork	x mm	330			
	1.9	Wheelbase	y mm	984	1.038	1.146	1.200
Weights	2.1.1	Service weight (incl. battery)	kg	2.490	2.570	2.760	2.870
	2.2	Axle load laden front/rear	kg	2.940 / 550	2.945 / 625	3.390 / 620	3.805 / 565
	2.3	Axle load unladen front/rear	kg	1.095 / 1.395	1.145 / 1.425	1.235 / 1.525	1.270 / 1.600
Wheels/suspension system	3.1	Tyres		SE			
	3.2	Tyre size, front		18 x 7-8			
	3.3	Tyre size, rear		18 x 7-8			
	3.5	Wheels, number front/back (x=driven)		2/1x			
	3.6	Tread width, front	b ₁₀ mm	838			
	3.7	Tread width, rear	b ₁₁ mm	0			
Basic dimensions	4.2	Retracted mast height (h1)	h ₁ mm	2.000			
	4.3	Free lift (h2)	h ₂ mm	150			
	4.4	Lift (h3)	h ₃ mm	3.000			
	4.5	Extended mast height (h4)	h ₄ mm	3.550			
	4.7	Height of overhead guard (cab)	h ₆ mm	2.090			
	4.8	Seat height/stand height	h ₇ mm	900			
	4.12	Coupling height	h ₁₀ mm	635			
	4.19	Overall length	l ₁ mm	2.719	2.773	2.881	2.935
	4.20	Length including fork shank	l ₂ mm	1.569	1.623	1.731	1.785
	4.21.1	2. Overall width (b2)	b ₁ mm	990			
	4.22	Fork dimensions	s/ e/l mm	35 / 100 / 1.150			
	4.23	Fork carriage connection class		2A			
	4.24	Fork carriage width	b ₃ mm	950			
	4.31	Ground clearance laden under mast	m ₁ mm	90			
	4.32	Ground clearance centre of wheelbase	m ₂ mm	100			
	4.34	Aisle width (pallet 1000x1200 sideways)	Ast mm	2.898	2.952	3.060	3.114
	4.34.1	Aisle width (pallet 800x1200 length)	Ast mm	3.020	3.074	3.182	3.236
	4.35	Turning radius	W ₉ mm	1.239	1.293	1.401	1.455
	4.36	Smallest pivot point distance	b ₁₃ mm	0			
Performance data	5.1	Travel speed laden/unladen	km/h	12 / 12.5			
	5.2	Lift speed laden/unladen	m/s	0.28 / 0.5	0.29 / 0.5	0.25 / 0.5	0.24 / 0.5
	5.3	Lowering speed laden/unladen	m/s	0.58 / 0.6			
	5.5	Drawbar pull laden/unladen	N	1.150 / 1.250		1.100 / 1.250	1.055 / 1.250
	5.6	Max. drawbar pull laden/unladen	N	4.400 / 4.500		4.375 / 4.500	4.350 / 4.500
	5.7	Gradeability laden/unladen	%	8.5 / 12	8 / 11.5	7 / 11	6.5 / 10.5
	5.8	Max. gradeability laden/unladen	%	13 / 18	12.5 / 17.5	11 / 16.5	10 / 16
	5.9	Acceleration time laden/unladen	s	5.1 / 4.6		5.4 / 4.7	5.6 / 4.8
	5.10	Service brake		hydraulic			

E-motor/Electronics	6.1	Drive motor, performance S2 60 min	kW	4			
	6.2	Lift motor, performance with S3	kW	6			
	6.3	Battery according to DIN 43531/35/36		DIN 43535 A			
	6.4	Battery voltage / nominal capacity	V / Ah	24 / 500	24 / 625	24 / 875	24 / 1.000
	6.5	Battery weight	kg	380	450	600	690
	6.6	Energy consumption according to VDI cycle	kWh/h	0			
	6.6.1	Energy consumption according to EN cycle	kWh/h	2.6		2.7	
	6.6.2	CO2 equivalent as per EN 16796	kg/h	1,40		1,46	
	6.7	Throughput	t/h	60		76	93
	6.8.1	Energy consumption with max. throughput	kWh/h	3.2	3.3	3.5	3.7
Miscellaneous	8.1	Type of drive control		Impulse/AC			
	10.1	Working pressure for attachment	bar	160		185	210
	10.2	Oil flow for attachments	l/min	14			
	10.7	Sound level as per EN12053, operator's ear	dB (A)	63			
	10.8	Trailer coupling, model/type DIN		DIN 15170 H			
- In accordance with VDI Guideline 2198 this data sheet provides details of the standard truck only. Non-standard tyres, different masts, optional equipment, etc. may result in different values.							

- 1.8: 337 mm for DZ mast; for integral sideshift: x = 362 mm (DZ mast 369 mm); for sideshift attachment: x = 390 mm (DZ mast 397 mm) - 6.6.1: 45 working cycles / h

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified.

ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet
European safety requirements.



 **JUNGHEINRICH**