

ENGLISH
FRANÇAIS
ESPAÑOL

NEW • NOUVEAUTÉ
NOVEDAD

Rex 4

70 - 80 - 90 - 100 - 110 - 120 F/GT



ENGLISH

		REX 4-070 F	REX 4-080 F-GT	REX 4-090 F-GT	REX 4-100 F-GT	REX 4-110 F-GT	REX 4-120 F-GT
ENGINE							
DEUTZ TIER 4 INTERIM		2.9 TCD L4	2.9 TCD L4	2.9 TCD L4	2.9 TCD L4	2.9 TCD L4	2.9 TCD L4
MAX POWER ISO	HP/KW	70/52	76/56	90/66	95/70	102/75	112/82
RATED SPEED	RPM	2200	2200	2200	2200	2200	2200
MAX TORQUE	NM	272	300	378	400	410	420
DISPLACEMENT/N° OF CYLINDERS	CM³	2900/4 TA	2900/4 TA	2900/4 TA	2900/4 TA	2900/4 TA	2900/4 TA
FUEL TANK CAPACITY F/GT	LT	80	80 / 90	80 / 90	80 / 90	80 / 90	80 / 90
CLUTCH							
INDEPENDENT DRY DUAL CLUTCH	IN.	11	11	12	12	12	12
MECHANICALLY OPERATED		●	●	●	●	●	●
MULTI-DISC WET CLUTCH		○	○	○	○	○	○
DE-CLUTCH CONTROL: BUTTON-OPERATED CLUTCH		○	○	○	○	○	○
TRANSMISSION							
SPEED FOUR + SYNCHRO SHUTTLE 12FWD+12RE V		●	●	●	●	●	●
SPEED FOUR + CREEPER + SYNCHRO SHUTTLE 16FWD+16REV		○	○	○	○	○	○
SPEED FOUR + POWER FOUR + CREEPER+ SYNCHRO SHUTTLE 32FWD+32REV		○	○	○	○	○	○
SPEED FOUR + REVERSE POWER SHUTTLE 12FWD+12REV		○	○	○	○	○	○
SPEED FOUR + CREEPER + REVERSE POWER SHUTTLE 16FWD+16REV		○	○	○	○	○	○
SPEED FOUR + POWER FOUR + CREEPER +REVERSE POWER SHUTTLE 32FWD+32REV		○	○	○	○	○	○
SPEED FOUR + T-TRONIC + REVERSE POWER SHUTTLE 36FWD+12REV		○	○	○	○	○	○
SPEED FOUR + T-TRONIC + CREEPER + REVERSE POWER SHUTTLE 48FWD+16REV		○	○	○	○	○	○
POWER TAKE-OFF							
POWER-ASSISTED BUTTON CONTROL		●	●	●	●	●	●
AUTO PTO WITH ELECTRONICALLY-OPERATED HITCH		○	○	○	○	○	○
2 SPEEDS PTO 540/540E RPM		●	●	●	●	●	●
2 SPEEDS PTO 540/1000 RPM		○	○	○	○	○	○
4 SPEEDS PTO 540/540E/1000/1000E RPM		○	○	○	○	○	○
1"3/8 (34,9 MM) PTO SHAFT WITH 6 SPLINES SYNCHRONIZED TO SPEED CHANGE		○	○	○	○	○	○
4WD FRONT AXLE							
ELECTROHYDRAULIC 4WD ENGAGEMENT		●	●	●	●	●	●
MAX. STEERING ANGLE		55°	55°	55°	55°	55°	55°
TWIN-LOCK ELECTROHYDRAULIC DIFF-LOCKS		○	○	○	○	○	○
LIMITED SLIP DIFF-LOCKS		●	●	●	●	●	●
SUSPENDED AXLE	F/GT	○	○/○	○/○	○/○	○/○	○/○
TWIN-LOCK ELECTROHYDRAULIC DIFF-LOCKS FOR SUSPENDED AXLE	F/GT	○	○/○	○/○	○/○	○/○	○/○
BRAKES							
WET MULTI-DISK REAR BRAKES		●	●	●	●	●	●
WET MULTI-DISK FRONT BRAKES		●	●	●	●	●	●
HYDRAULIC TRAILER BRAKES		○	○	○	○	○	○
REAR HYDRAULIC POWER LIFT							
DRAFT, POSITION, INTERMIX AND FLOATING CONTROL FUNCTIONS		●	●	●	●	●	●
MECHANICALLY OPERATED		●	●	●	●	●	●
E.L.S. ERGONOMIC LIFT SYSTEM		○	○	○	○	○	○
ELECTRONICALLY		○	○	○	○	○	○
MAX. LIFT CAPACITY	KG	2700	2700	2700	2700	2700	2700
ADDITIONAL CAPACITY WITH 1 ASSISTOR RAM. (ONLY FOR GT MODEL)	KG	-	3400	3400	3400	3400	3400
HYDRAULIC FLOW (LIFT+STEERING)	L/MIN	50 + 28	50+28	50+28	50+28	50+28	50+28
CATEGORY 2 THREE-POINT LINKAGE		●	●	●	●	●	●
HYDRAULIC ADJUSTMENT OF RIGHT LIFTING ROD		○	○	○	○	○	○
REMOTE VALVES STD		2	2	2	2	2	2
MID-MOUNTED REMOTE VALVES		○	○	○	○	○	○
TRIPLE PUMP FLOW RATE (STEERING+LIFT +VALVES)	L/MIN	28+41+41	28+41+41	28+41+41	28+41+41	28+41+41	28+41+41
TRIPLE PUMP + 3 FRONT REMOTE VALVES + JOYSTICK		○	○	○	○	○	○
FRONT HYDRAULIC POWER LIFT							
LIFT CAPACITY	KG	1400	1400	1400	1400	1400	1400
FRONT PTO 1000 RPM		○	○	○	○	○	○
CAB AND DRIVING SEAT							
"TOTAL VIEW" CAB / RADIO ADAPTOR		●	●	●	●	●	●
FILTER CATEGORY	STD / OPT	2 / 4	2 / 4	2 / 4	2 / 4	2 / 4	2 / 4
HEATING/VENTILATION		●	●	●	●	●	●
AIR-CONDITIONING		●	●	●	●	●	●
DIMENSIONS AND WEIGHTS							
LENGHT 4WD	MM	4370	4370	4370	4370	4370	4370
MIN. WIDTH	MM	1342	1342 / 1478	1342 / 1478	1342 / 1478	1342 / 1478	1342 / 1478
WHEELBASE 4WD	MM	2140	2140	2140	2140	2140	2140
MIN. HEIGHT OVER CAB	MM	2400	2400	2400	2400	2400	2400
MIN. GROUND CLEARANCE 4RM	MM	250	250 / 250	250 / 250	250 / 250	250 / 250	250 / 250
WEIGHT 4WD WITHOUT WEIGHTS	KG	2800	2800/3000	2800/3000	2800/3000	2800/3000	2800/3000
OPTIONAL EQUIPMENT							
6 FRONT WEIGHTS (36 KG) EACH		○	○	○	○	○	○
4 FRONT WEIGHTS (42 KG) EACH		○	○	○	○	○	○

Key: ● standard ○ option – not available

All data and illustrations provided in this brochure are for information purposes only and can be changed without notice.