

ENGLISH
FRANÇAIS
ESPAÑOL

NEW • NOUVEAUTÉ
NOVEDAD

Rex 4

70 - 80 - 90 - 100 - 110V



ENGLISH

		REX 4-070V	REX 4-080V	REX 4-090V	REX 4-100V	REX 4-110V
ENGINE						
DEUTZ TIER 4 INTERIM		2,9 TCD L4	2,9 TCD L4	2,9 TCD L4	2,9 TCD L4	2,9 TCD L4
MAX POWER ISO	HP/KW	70/52	76/56	90/66	95/70	102/75
RATED SPEED	RPM	2200	2200	2200	2200	2200
MAX.TORQUE	NM	272	300	378	400	410
DISPLACEMENT/N° OF CYLINDERS	CM ³	2900/4 TA	2900/4 TA	2900/4 TA	2900/4 TA	2900/4 TA
FUEL TANK CAPACITY	LT	80	80	80	80	80
CLUTCH						
INDEPENDENT DRY DUAL CLUTCH	IN.	11	11	12	12	12
MECHANICALLY OPERATED		●	●	●	●	●
MULTI-DISC WET CLUTCH		○	○	○	○	○
DE-CLUTCH CONTROL: BUTTON-OPERATED CLUTCH		○	○	○	○	○
TRANSMISSION						
SPEED FOUR + SYNCHRO SHUTTLE 12FWD+12REV		●	●	●	●	●
SPEED FOUR + CREEPER + SYNCHRO SHUTTLE 16FWD+16REV		○	○	○	○	○
SPEED FOUR + POWER FOUR + CREEPER+ SYNCHRO SHUTTLE 32FWD+32REV		○	○	○	○	○
SPEED FOUR + REVERSE POWER SHUTTLE 12FWD+12REV		○	○	○	○	○
SPEED FOUR + CREEPER + REVERSE POWER SHUTTLE 16FWD+16REV		○	○	○	○	○
SPEED FOUR + POWER FOUR + CREEPER +REVERSE POWER SHUTTLE 32FWD+32REV		○	○	○	○	○
SPEED FOUR + T-TRONIC + REVERSE POWER SHUTTLE 36FWD+12REV		○	○	○	○	○
SPEED FOUR + T-TRONIC + CREEPER + REVERSE POWER SHUTTLE 48FWD+16REV		○	○	○	○	○
POWER TAKE-OFF						
POWER-ASSISTED BUTTON CONTROL		●	●	●	●	●
AUTO PTO WITH ELECTRONICALLY-OPERATED HITCH		○	○	○	○	○
2 SPEEDS PTO 540/540E RPM		●	●	●	●	●
2 SPEEDS PTO 540/1000 RPM		○	○	○	○	○
4 SPEEDS PTO 540/540E/1000/1000E RPM		○	○	○	○	○
1"3/8 (34,9 MM) PTO SHAFT WITH 6 SPLINES		●	●	●	●	●
SYNCHRONIZED TO SPEED CHANGE		○	○	○	○	○
4WD FRONT AXLE						
ELECTROHYDRAULIC 4WD ENGAGEMENT		●	●	●	●	●
MAX. STEERING ANGLE		55°	55°	55°	55°	55°
LIMITED SLIP DIFF-LOCKS		●	●	●	●	●
BRAKES						
WET MULTI-DISK REAR BRAKES		●	●	●	●	●
WET MULTI-DISK FRONT BRAKES		●	●	●	●	●
HYDRAULIC TRAILER BRAKES		○	○	○	○	○
REAR HYDRAULIC POWER LIFT						
DRAFT, POSITION, INTERMIX AND FLOATING CONTROL FUNCTIONS		●	●	●	●	●
MECHANICALLY OPERATED		●	●	●	●	●
E.L.S. ERGONOMIC LIFT SYSTEM		○	○	○	○	○
ELECTRONICALLY		○	○	○	○	○
MAX. LIFT CAPACITY	KG	2700	2700	2700	2700	2700
HYDRAULIC FLOW (LIFT+STEERING)	L/MIN	50+28	50+28	50+28	50+28	50+28
CATEGORY 2 THREE-POINT LINKAGE		●	●	●	●	●
HYDRAULIC ADJUSTMENT OF RIGHT LIFTING ROD		○	○	○	○	○
REMOTE VALVES STD		2	2	2	2	2
MID-MOUNTED REMOTE VALVES		○	○	○	○	○
TRIPLE PUMP FLOW RATE (STEERING+LIFT+VALVES)	L/MIN	28+41+41	28+41+41	28+41+41	28+41+41	28+41+41
TRIPLE PUMP + 3 FRONT REMOTE VALVES + JOYSTICK		○	○	○	○	○
FRONT HYDRAULIC POWER LIFT						
LIFT CAPACITY	KG	1400	1400	1400	1400	1400
FRONT PTO 1000 RPM		○	○	○	○	○
CAB AND DRIVING SEAT						
"TOTAL VIEW" CAB / RADIO ADAPTOR		●	●	●	●	●
FILTER CATEGORY	STD/OPT	2 / 4	2 / 4	2 / 4	2 / 4	2 / 4
HEATING/VENTILATION		●	●	●	●	●
AIR-CONDITIONING		●	●	●	●	●
DIMENSIONS AND WEIGHTS						
LENGHT 4WD	MM	4370	4370	4370	4370	4370
MIN. WIDTH	MM	1000	1000	1000	1000	1000
WHEELBASE 4WD	MM	2140	2140	2140	2140	2140
MIN. HEIGHT OVER CAB	MM	2400	2400	2400	2400	2400
MIN. GROUND CLEARANCE 4RM	MM	250	250	250	250	250
WEIGHT 4WD WITHOUT WEIGHTS	KG	2800	2800	2800	2800	2800
OPTIONAL EQUIPMENT						
6 FRONT WEIGHTS 36 KG EACH		○	○	○	○	○
4 FRONT WEIGHTS 42 KG EACH		○	○	○	○	○

Key: ● standard ○ option – not available

All data and illustrations provided in this brochure are for information purposes only and can be changed without notice.